Application/Control Number: 10/010,965

Art Unit: ***

Page 2

CLMPTO-05/16/03

1. (Original) A spread illuminating apparatus comprising:

a light conductive plate shaped substantially rectangular and made of a light-transmissible

material;

a spot-like light source disposed close to or in contact with a light entrance surface formed at

either a side surface or a corner of said light conductive plate;

a light reflection pattern formed on a major surface of said light conductive plate and

including a plurality of grooves which each extend so as to shape a substantially minor are

with respect to said spot-like light source and which are arrayed concentrically; and

a plurality of lenticular elements made of a light-transmissible material, provided on a major

surface of said light conductive plate opposite to said major surface provided with said light

reflection pattern, and having their respective longitudinal directions oriented perpendicular

to said plurality of grooves of said light reflection pattern.

2. (Original) A spread illuminating apparatus as set forth in Claim 1, wherein each of

said lenticular elements is rectangular in top plan view.

3. (Original) A spread illuminating apparatus as set forth in Claim 1, wherein each of

said lenticular elements is substantially trapezoidal in top plan view, and which have their

respective shorter sides of two parallel sides facing said spot-like light source.

Page 3

Art Unit: ***

4. (Currently Amended) A spread illuminating apparatus as set forth in any one-of-Claims 1 to 3, wherein said lenticular elements are of various lengths measuring in a wide range.

- 5. (Currently Amended) A spread illuminating apparatus as set forth in any-one of Claims 1-to-4, wherein said lenticular elements are mostly of a length identical with one another except a smaller number thereof being of various lengths measuring in a narrow range.
- 6. (Currently Amended) A spread illuminating apparatus as set forth in any one of Claims 1-to-5, wherein said lenticular elements each have a cross section outlined by a minor are and a chord connecting two points both defining said minor are.
- 7. (Original) A spread illuminating apparatus as set forth in Claim 6, wherein said lenticular elements each have their respective widths and heights set such that view field angles thereof range from 5 degrees to 20 degrees preferably 10 degrees to 20 degrees.
- 8. (Currently Amended) A spread illuminating apparatus as set forth in any-one-of Claims 1-to-7, wherein said lenticular elements and said light conductive plate are formed integrally of one same material.
- 9. (Currently Amended) A spread illuminating apparatus as set forth in any one of Claims 1-to-7, wherein said lenticular elements and said light conductive plate are formed discretely.